

DIGITAL CAMERA		Digital IXUS 980 IS
IMAGE SENSOR		
Type		1/1.7" CCD
Effective Pixels		Approx.14.7M
Colour Filter Type		Primary Colour
IMAGE PROCESSOR		
Type		DIGIC 4 with iSAPS technology
LENS		
Focal Length		7.7 - 28.5 mm (35mm equivalent: 36 – 133mm)
Zoom		Optical 3.7x. Digital approx. 4x (with Digital Tele-Converter approx. 1.7x or 2.2x and Safety Zoom (1)) (2). Combined approx. 15x
Maximum f/number		f/2.8 – f/5.8
Construction		7 elements in 5 groups (2 aspherical elements including 1 double-sided UA element)
Image Stabilisation		Yes (shift-type)
FOCUSING		
Type		TTL
AF System/ Points		AiAF (Face Detection / 9-point), 1-point AF (fixed to centre or Face Select and Track)
AF Modes		Single, Servo AF(10)
AF Point Selection		Size (Normal, Small)
AF Lock		On/Off Selectable
AF Assist Beam		Yes
Manual Focus		Yes
Closest Focusing Distance		5cm (W) from front of lens in macro
EXPOSURE CONTROL		
Metering modes		Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (centre)
AE Lock		On/Off Selectable
Exposure Compensation		+/- 2 EV in 1/3 stop increments. i-Contrast for automatic dynamic range correction
ISO sensitivity (3)		AUTO, High ISO Auto (incorporating Motion Detection Technology), 80, 100, 200, 400, 800, 1600
SHUTTER		
Speed		1/60 - 1/1600 sec (factory default) 15 - 1/1600 sec (total range - varies by shooting mode)
WHITE BALANCE		
Type		TTL
Settings		Auto (including Face Detection WB), Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
VIEWFINDER		
Viewfinder		Real-image zoom, optical viewfinder
LCD MONITOR		
Monitor		2.5" PureColor LCD II (TFT), approx. 230,000 dots
Coverage		100%
Brightness		Adjustable to one of fifteen levels
FLASH		
Modes		Auto, Manual Flash On / Off
Slow Sync Speed		Yes
Red-Eye Reduction		Yes
Flash Exposure Compensation		+/- 2 EV in 1/3 stop increments. Face Detection FE.
Flash Exposure Lock		Yes
Manual Power Adjustment		3 levels with internal flash
Built-in Flash Range		50cm - 4.6m (W) / 2.4m (T)
External Flash		Canon High Power Flash HF-DC1
SHOOTING		
Modes		Auto, P, M, Quick, Movie, Special Scene (Portrait, Night Snapshot, Kids & Pets, Indoor, Sunset, Foliage, Snow, Beach, Fireworks, Aquarium, Underwater, ISO 3200(5), Digital Macro, Color Accent, Color Swap, Stitch Assist)

Photo Effects	My Colors (My Colors Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter Skin Tone, Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)
Drive modes	Single, Continuous, Self-Timer, FaceSelf-Timer
Continuous Shooting	Approx. 1.3 shots/sec.(6) (until memory card becomes full)(7)
RECORDING PIXELS / COMPRESSION	
Image Size	(L) 4416 x 3312, (M1) 3456 x 2592, (M2) 2592 x 1944, (M3) 1600 x 1200, (S) 640 x 480, (W) 4416 x 2480. Resize in playback (M3, S, 320 x 240)
Compression Movies	Superfine, Fine, Normal 640 x 480, 30fps 320 x 240, 30fps
Movie Length	Up to 4GB or 1 hour (7)
FILE TYPES	
Still Image Type	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant
Movies Sound Files	MOV [H.264 + Linear PCM (monaural)] WAVE (monaural)
DIRECT PRINT	
Canon Printers	Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print supported on SELPHY CP & ES printers only)
PictBridge	Yes
OTHER FEATURES	
Red-Eye Correction My Camera / My Menu	Yes, during shooting and playback Start-up image and camera sounds customisation
My Category Sound Memo Intelligent Orientation Sensor Histogram Playback zoom Self Timer	Image tagging feature Up to 60 sec per image Yes Yes, live histogram Approx. 2x – 10x Approx. 2 or 10 sec., Custom or FaceSelf-Timer
Menu Languages	English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Simplified Chinese, Chinese (traditional), Japanese, Russian, Portuguese, Korean, Greek, Polish, Czech, Hungarian, Turkish, Thai, Arabic, Ukrainian, Romanian, Farsi
INTERFACE	
Computer	Hi-Speed USB (MTP, PTP) dedicated connector (Mini-B compatible)
Other	A/V output, dedicated connector (PAL/NTSC)
MEMORY CARD	
Type	SD, SDHC, MMC, MMCplus, HC MMCplus. 32MB memory card supplied
SUPPORTED OPERATING SYSTEM	
PC & Macintosh	Windows XP SP2 / Vista (including SP1) Mac OS X v10.4 - 10.5
SOFTWARE	
Browsing & Printing Other	ZoomBrowser EX / ImageBrowser PhotoStitch
POWER SOURCE	
Batteries	Rechargeable Li-ion Battery NB-5L (battery and charger supplied)
Battery life	Approx. 280 shots (8) Approx. 360 min. playback
A/C Power Supply	Optional, AC adapter kit ACK-DC30
ACCESSORIES	
Case	Soft Leather Case DCC-70, Digital IXUS Metal or Leather Strap

Waterproof / Weatherproof Case	Waterproof Case (40m) WP-DC27, Waterproof Case Weight WW-DC1
Flash	High Power Flash HF-DC1
Power Supply & Battery Chargers	AC Adapter Kit ACK-DC30
PHYSICAL SPECIFICATIONS	
Operating Environment	0 – 40 °C, 10 – 90% humidity
Dimensions (WxHxD)	96.7 x 62.2 x 27.9mm
Weight (body only)	Approx. 160g

All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated. Subject to change without notice.

- (1) Depending on the image size selected.
- (2) Digital zoom available for still image and standard movie modes only. Optical zoom may not be available during movie recording.
- (3) Standard Output Sensitivity / Recommended Exposure Index. According to ISO 12232:2006 (20th April 2006) which specifies the method for assigning and reporting ISO speed ratings for digital still cameras.
- (5) Recording pixels fixed at 1600 x 1200.
- (6) Under conditions where the flash does not fire.
- (7) Depending on memory card speed / capacity.
- (8) Using the batteries and memory card format supplied with the camera, except where indicated.
- (10) Some settings limit availability