



**EF 400mm f/2.8L IS II USM  
Specification Sheet**

**Optical Features/Specifications**

Angle of view (horizontal, vertical, diagonal)	5°10', 3°30', 6°10'
Lens construction (elements/groups)	16/12
No. of diaphragm blades	9
Minimum aperture	32
Closest focussing distance (m)	2.7
Maximum magnification (x)	0.17
Distance Information	Provided
Image stabilizer	4-stops
AF actuator	Ring USM <sup>3</sup>

**Physical Specifications**

Dust/moisture resistance <sup>4</sup>	Yes
Filter diameter (mm)	52 Drop in
Max. diameter x length (mm)	163 x 343
Weight (g)	3850

**Accessories**

Lens Cap	E-180D
Lens hood	ET-155(WII)
Lens case/pouch	Hard case 400C
Maximum number of Hood III compatible with Gelatin Filter Holder III	NC <sup>8</sup>
Maximum number of Hood IV compatible with Gelatin Filter Holder IV	NC <sup>8</sup>
Magnification with Extension Tube EF12 II	0.21-0.03
Magnification with Extension Tube EF25 II	0.26-0.07
Extender Compatibility	Compatible
Other Accessories	Canon drop-in 52mm filters

All data is based on Canon standard testing methods except where indicated.  
Subject to change without notice.

<sup>3</sup> Full time Manual focus

<sup>4</sup> Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

<sup>8</sup> Use 52mm drop in filter holder