

DIGITAL CAMERA	Specifications	EOS-1D Mark III
IMAGE SENSOR		
	Type	28.1 x 18.7 mm CMOS
	Effective Pixels	Approx. 10.1M
	Total Pixels	Approx. 10.7M
	Aspect Ratio	3:2
	Low-Pass Filter	Built-in/Fixed with Self Cleaning Sensor Unit
	Colour Filter Type	Primary Colour
IMAGE PROCESSOR		
	Type	2 x DIGIC III
LENS		
	Lens Mount	EF (excludes EF-S lenses)
	Focal Length	1.3x Multiplication with EF lens fitted
FOCUSING		
	Type	TTL-AREA-SIR with a CMOS sensor
	AF System/ Points	19 cross-type AF points (plus 26 Assist AF points)
	AF working range	EV -1 - 18 (at 23°C & ISO 100)
	AF Modes	One Shot AI Servo
	AF Point Selection	Automatic selection, Manual selection, Home position (switch to registered AF point)
	Selected AF point display	Superimposed in viewfinder
	Predictive AF	Yes
	AF Lock	Locked when shutter button is pressed half way in One Shot AF mode.
	AF Assist Beam	Emitted by an optional dedicated Speedlite
	Manual Focus	Selected on lens, default in Live View Mode
EXPOSURE CONTROL		
	Metering modes	TTL full aperture metering with 63 zone SPC (1) Evaluative metering (linked to any AF point) (2) Partial metering (approx. 13.5% of viewfinder at centre) (3) Spot metering: Center spot metering (approx. 3.8% viewfinder at center) AF point-linked spot metering (approx. 3.8% of viewfinder) Multi/Spot metering (Max 8 spot metering entries) (4) Center weighted average metering
	Metering Range	EV 0 - 20 (at 23°C with 50mm f1.4 lens ISO 100)
	AE Lock	Auto: Operates in 1-shot AF mode with evaluative metering when focus is achieved Manual: By AE lock button in all metering modes
	Exposure Compensation	+/-3 EV in 1/3 or 1/2 stop increments (can be combined with AEB).
	AEB	+/-3 EV in 1/3-stop increments. 1/2-stop increments selectable with C.Fn I - 01
	ISO Speed Equivalent	100-3200 (in 1/3-stop increments) ISO can be expanded to L: 50 or H: 6400 (selected with C.Fn I -03) ISO 200-3200 in Highlight Tone Priority (C.Fn II -03)
SHUTTER		
	Type	Electronically-controlled focal-plane shutter

	Speed Shutter release	30 - 1/8000 sec. (1/3 stop increments), Bulb Soft touch electromagnetic release
WHITE BALANCE		
	Type Settings	Auto white balance with the imaging sensor Auto, Daylight, Shade, Cloudy, Tungsten light, White Fluorescent light, Flash, Custom (5 settings), Colour Temperature Setting, Personal WB White balance compensation: 1. Blue/Amber +/-9 2. Magenta/ Green +/-9.
	Personal White Balance WB Bracketing	5 personal WB settings can be registered +/-3 stops in full stop increments. 3 bracketed images per shutter release. Method: 1. Blue/Amber 2.Magenta/Green.
COLOUR MATRIX		
	Type	Two types of colour space, sRGB and Adobe RGB.
VIEWFINDER		
	Viewfinder Coverage (Vertical/Horizontal) Magnification Eyepoint Dioptre Correction Focusing Screen	Pentaprism Approx. 100% 0.76x (4) 20mm -3 to +1 dpt Interchangeable (10 types). Standard Focusing Screen Ec-C IV
	Mirror	Quick-return half mirror (Transmission: reflection ratio of 37:63, no mirror cut-off with EF1200mm f5.6 or shorter)
	Viewfinder Information	AF information (AF points, focus confirmation light), Exposure information (metering mode, shutter speed, aperture, manual exposure, spot metering circle, AE lock, ISO speed, exposure level, exposure warning), Flash information (flash ready, FP flash, FE lock, flash exposure level), white balance correction, JPEG recording, RAW recording, number of remaining shots, maximum burst, memory card information, battery check icon.
	Depth of field preview Eyepiece shutter	Yes Built-in
LCD MONITOR		
	Monitor	3.0" TFT, approx. 230K pixels Live View Mode with selectable grid and aspect ratio markings.
	Coverage Brightness	Approx. 100% Adjustable to one of seven levels
FLASH		
	Modes HotShoe/ PC terminal X-sync Flash Exposure Compensation Flash Exposure Bracketing Flash Exposure Lock Second Curtain Synchronisation External Flash	E-TTL II Auto Flash, Metered Manual Yes/ Yes 1/300sec (EX series Speedlites only) +/-3 EV in 1/3 or 1/2 stop increments with EX series Speedlites Yes Yes Yes E-TTL II with EX series Speedlites, wireless multi-flash support.

SHOOTING		
	Modes	Program AE, Shutter priority AE, Aperture priority AE, Manual
	Photo Effects	Monochrome (selected from the "Picture Style" menu) with options for Filters and Toning Effects.
	Drive modes	Single / Silent / Continuous L/ Continuous H
	Continuous Shooting	Max. Approx.10fps. (speed maintained for up to 110 images (JPEG), 30 images (RAW)) (2)
RECORDING PIXELS / COMPRESSION		
	Image Size	(L)3888x2592, (M1)3456x2304, (M2)2816x1880, (S)1936x1288, (RAW)3888x2592, (sRAW)1936x1288
	Compression	JPEG (1-10 settings, user selectable), RAW / sRAW (Canon RAW 2nd edition)
FILE FORMAT		
	Still Image Format	JPEG (Exif 2.21 [Exif Print] compliant) / Design rule for Camera File system (2.0), Digital Print Order Format [DPOF] Version 1.1 compliant
	RAW+JPEG simultaneous recording	Yes (separate formats to sperate cards)
	Folders	Folder creation & selection is possible
	File Numbering	(1) Consecutive numbering (2) Auto reset (3) Manual reset
	Processing Parameters	6 Preset 'Picture Style' modes with 3 User defined settings
	Sound Files	WAVE (monaural)
DIRECT PRINT		
	Canon Printers	Canon Compact Photo Printers and PIXMA Printers supporting PictBridge
	PictBridge	Yes
OTHER FEATURES		
	Custom Functions	57 Custom Functions with 156 settings
	Personal Functions	No
	LCD Panel (EL)	Yes
	Illumination	Yes
	Water/ Dust resistance	Yes
	Sound Memo	Up to 30sec per image
	Intelligent Orientation Sensor	Yes
	Histogram	Brightness: Yes RGB: Yes
	Playback zoom	1.5x - 10x
	Display Formats	(1)Single image with information (inc. file size) (2) Single image (3) 4 image index (4) 9 image index (5) Magnified view
	Image Erase Protection	Erase protection of one image, all images in a folder, or all images in the memory card can be applied or cancelled at one time
	Image Erase	Single image, All images (card / folder), Checkmarked images
	Self Timer	Approx. 2 or 10 sec.

	Menu Categories	(1) Recording menu (2) Playback menu (3) Set-up menu (4) Custom Functions menu (5) My Menu
	Menu Languages	English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Simplified Chinese, Japanese, Traditional Chinese, Korean, Russian, Polish
	Firmware Update	Update possible by the user.
INTERFACE		
	Computer	USB 2.0 Hi-Speed (Mini-B)
	Other	Video output (PAL/ NTSC), 15-pin System Extension
MEMORY CARD		
	Type	CompactFlash Type I/ II (Microdrive compatible)(3), SDHC (3), SD memory (up to 2GB), External Media (with Wireless File Transmitter WFT-E2 only).
SUPPORTED OPERATING SYSTEM		
	PC & Macintosh	Windows 2000 (SP4) / XP (SP2) / Vista OS X v10.3-10.4
SOFTWARE		
	Browsing & Printing	ZoomBrowser EX / ImageBrowser
	Other	PhotoStitch, EOS Utility* (inc. Remote Shooting) * Requires OS X 10.4.7 on an Intel Mac
	Drivers	PTP TWAIN Driver (Windows 2000 / XP)
	Image Manipulation	Digital Photo Professional (RAW Image Processing)
POWER SOURCE		
	Batteries	1x Li-ion pack LP-E4, 1x CR2025 for date & settings
	Battery life	Approx. 2200 (at 23C) (5) Approx. 1700 (at 0C)
	Battery check	Automatic
	Power saving	Power turns off after 1, 2, 4, 8, 15 or 30mins.
	A/C Power Supply	Power adapter ACK-E4
ACCESSORIES		
	Case	All EF lenses (excludes EF-S lenses) Canon Speedlites (220EX, 380EX, 420EX, 430EX, 550EX, 580EX, 580EX II, Macro-Ring-Lite, MR-14EX, Macro Twin Lite MT-24EX, Speedlite Transmitter ST-E2) Remote control with N3 type contact, Wireless Controller LC-5 Battery Pack LP-E4, Battery charger LC-E4, Car Battery Cable CG-570 (use with LC-E4), Power Adapter ACK-E4 Wireless File Transmitter WFT-E2, Original Data Security Kit OSK-E3, Eyecup Eg, Eg-series Dioptic Adjustment Lens with Rubber Frame Eg, Anti Fog Eyepiece Eg, Focusing Screens Ec, Angle Finder C, Hand Strap E1
	Lenses	
	Flash	
	Remote Controller/ Switch	
	Power Supply & Battery Chargers	
	Other	
PHYSICAL SPECIFICATIONS		
	Body Materials	Magnesium Alloy
	Operating Environment	0-45 °C, 85% or lower humidity
	Dimensions (WxHxD)	156.0 x 156.6 x 79.9mm
	Weight (body only)	Approx. 1155g (battery weight 180g)

1 Large/Fine resolution

2 Depending on memory card speed / capacity

3 Compatible with large memory card capacities, including cards of 2GB and more (camera may require firmware update).

4 with 50mm lens at infinity, -1 dpt

5 Based on the CIPA Standard and using the batteries and memory card format supplied with the camera, except where indicated