

i-SENSYS MF8350Cdn Specifications Sheet	
Machine type	Colour Laser All-In-One
Available functions	Print, Copy, Scan and Fax
Printer	
Print speed	Up to 20 ppm colour and mono (A4)
Printing method	Colour laser beam printing
Print quality	Up to 2400 x 600 dpi with Automatic Image Refinement
Print resolution	600 x 600 dpi
Double sided printing	Automatic
Printer languages	UFR II-LT
Print margins	5 mm-top, bottom, left and right
Toner saver mode	Yes
Copier	
Copy speed	Up to 20 cpm colour and mono (A4)
First Copy Output Time (FCOT)	Approx. 16 seconds or less
Copy resolution	Up to 600 x 600 dpi
Copy modes	Text/Photo/Map (Default), Text/Photo/Map (quality), Printed Image, Text
Double sided copying	1-sided to 2-sided (Manual)
Multiple copy	Up to 99 copies
Reduction / Enlargement	25-400% in 1% increments
Other features	Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy
SEND Functions	
Scan to USB memory key	Yes
File formats	PDF
Scanner	
Type	Colour
Scan resolution	Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi
Colour scanning depth	24 bit/24 bit (input/output)
Greyscales	256 levels
Compatibility	TWAIN , WIA
Max. scan width	216 mm
Fax	
Modem speed	Super G3 33.6kbps (Up to 3 seconds/page ¹)
Receive mode	Fax only, Fax/Tel Auto Switch, Answer Mode, Manual RX
Fax resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi
FAX memory	Up to 512 pages ¹
Speed dials	Max. 200 (including 19 one-touch dials)
Group dials/destinations	Max. 199 dials / Max. 199 destinations
Sequential broadcast	Max. 201 locations
Memory backup	5 mins
Double sided faxing	Yes (Receive/ Transmit (Manual))
Other features	Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only)
Media handling	
Scanner type	Flatbed and Automatic Document Feeder (ADF)
Paper input (Standard)	250-sheet cassette 50-sheet multi-purpose tray 50-sheet ADF
Paper input (Option)	250-sheet cassette
Paper output	125-sheet

Media types	Plain paper, Recycled paper, Heavy Paper, Transparency, Coated Paper, Label, Index card, Envelope
Media sizes	Cassette and optional cassette : A4, A5, B5, Legal, Letter, Executive, Statement, Envelope (COM10, DL, ISO-C5, ISO-B5), Custom sizes: Width 100 to 215.9 mm; Length 148 to 355.6 mm. Multi-purpose tray: A4, A5, B5, Legal, Letter, Executive, Statement, Envelope (COM10, Monarch, DL, ISO-C5, ISO-B5), Custom sizes: Width 76.2 to 215.9 mm; Length 127.0 to 355.6 mm. ADF: A4, A5, B5, Legal, Letter, Statement, Custom sizes (W x L): Max 215.9 mm x 355.6 mm Min. 128 mm x 139.7 mm
Media weights	Cassette: 60 to 163 g/m ² Manual feed slot: 60 to 220 g/m ² ADF: 50 to 105 g/m ²
Interface & Software	
Interface type	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX
Operating System compatibility	Windows 2000/Server 2003/ Server 2008/ XP/ Vista Mac OS X version 10.4.9- 10.5.x ^{2 3}
Software and printer management	Presto! Page Manager, MF Toolbox, NetSpot Device Installer, Remote User Interface (RUI), Department ID Management
General features	
Duty cycle	Max. 40,000 pages per month
Warm-up Time	Approx. 23 seconds from power on
Memory	128MB (shared)
Control panel	5 lines backlit LCD
Dimensions with trays (W x D x H)	430 mm x 484 mm x 479 mm
Installation space (W x D x H)	674 mm x 1327 mm x 851 mm 679 mm x 1327 mm x 951 mm (with optional 250-sheet paper cassette)
Weight	Approx. 31 Kg
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Power Source	220-240V(±10%) 50/60Hz (±2Hz)
Power Consumption	Maximum: Approx. 1200 W Standby: Approx. 25 W Sleep mode: Approx. 3 W Typical Electricity Consumption (TEC): 1.0 kWh/week
Noise Levels	Sound Pressure ⁴ : Active: 67 dB(A) or less Standby: 46 dB(A) or less
Consumables	
Cartridges	Cartridge 718 Black (3,400 pages ⁵⁾ ⁶ Cartridge 718 Cyan (2,900 pages ⁵⁾ ⁶ Cartridge 718 Magenta (2,900 pages ⁵⁾ ⁶ Cartridge 718 Yellow (2,900 pages ⁵⁾ ⁶
Accessories/ options	
Items	CST.FEEDING UNIT-V1 (250-sheet cassette) TEL 6 KIT LONG CORD (Telephone handset)

Standard disclaimers	All specifications subject to change without notice
[1]	Based on ITU-T Standard Chart No. 1
[2]	Web distribution only
[3]	Network scanning not supported
[4]	Declared noise emission in accordance with ISO 9296
[5]	Based on ISO/IEC 19798
[6]	Printer ships with 1,200 pages K (Black) and 1,400 pages CMY (Cyan, Magenta and Yellow) starter cartridges