

Large Format Print Solutions ideal for CAD & GIS

iPF650 / iPF655

you can

The **imagePROGRAF iPF650 and iPF655** are 24" large format printers, designed for high quality, outstanding accuracy and productivity for greater return on investment.

iPF650 / iPF655 24 INCH
2,400 X 1,200DPI
ECONOMY PRINTING MODE
5 COLOURS
A1 30 SECONDS
160GB HDD (iPF655)
15,360 NOZZLES
BORDERLESS PRINTING



Key Features

- Manage costs and track ROI - Full accounting and eMaintenance software included.
- High capacity basket with stacking functionality to prevent damage to prints.
- Space saving - Unique compact design to fit anywhere.
- User Friendly - Simple roll paper loading system and control the print from the front.
- Maximise productivity - "Hot Swap" ink tanks, changeable during production
- Minimise printer downtime with media mismatch detection (iPF655).
- Highly accurate with 0.02mm minimum line width and +/-0.1% line accuracy.
- Integrate with your office applications with Microsoft Office Plug-in.
- HP-GL/2 and HP-RTL Compatible: - Capable of handling large vector files - HP-GL/2 pallet and pen settings - HP-GL/2 and HP-RTL nesting (iPF655). - HP-GL/2 auto-rotation.

 **imagePROGRAF**

Canon

Specifications: iPF650 / iPF655

Class	24-inch
Ink Type	Pigment and Dye reactive ink, 5 colours (MBK x 2, BK, C, M, Y)
Maximum Print Resolution	2,400 x 1,200dpi
Printing Speed (A1 Roll, Full Colour Image)	
Plain Paper	0.30 (Draft mode)
Coated Paper	0.43 (Standard Mode) 0.43 (Draft Mode)
Dimensions, Weight (Net)	1.18 (Standard Mode) 2.06 (High Quality Mode)
W x D x H (mm), (kg)	iPF650: Main unit only 997(W) x 698(D) x 507(H)mm; Weight: approx. 43.4kg iPF655: Main unit only 997(W) x 698(D) x 507(H)mm; Weight: approx. 43.6kg iPF650: Main unit with a basket open and a printer stand 997(W) x 870(D) x 1,062(H)mm; Weight: approx. 53.7kg (roll holder included, no inks, no print heads) iPF655: Main unit with a basket open and a printer stand 997(W) x 870(D) x 1,062(H)mm; Weight: approx. 53.9kg (roll holder included, no inks, no print heads)
Dimensions, Weight (Packaged)	
W x D x H (mm), (kg)	iPF650: Main unit 1,127(W) x 830(D) x 762(H)mm; Weight: approx. 63kg iPF655: Main unit 1,127(W) x 830(D) x 762(H)mm; Weight: approx. 63.2kg iPF650: Stand and Basket 1,073(W) x 766(D) x 263(H)mm; Weight: approx. 15.8kg iPF655: Stand and Basket 1,073(W) x 766(D) x 263(H)mm; Weight: approx. 15.8kg
Power Supply	
Input power	AC 100 - 240 V (50/60 Hz)
Power consumption	140 W or less
Standby power consumption (At the low power mode)	
220 V - 240 V	6 W or less
100 V - 120 V	5 W or less
Power off (standby)	1 W or less (In compliance with Executive Order of the President of the United States of America)
Operational Environment	
Acoustic pressure	Temperature: 15 - 30°C, Humidity: 10 - 80% (Condensation free)
Acoustic power	Operation: 47 dB (A) or less, Standby: 35 dB (A) or less
Minimal Line Width	Operation: 6.4 Bels or less
Line Accuracy	0.02mm (Theoretical value)
Operation Panel Display	±0.1 % or less (User adjustments necessary. Printing environment media must match that used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only.)
Language on operation panel	Large LCD: 160 x 128 dots, Key x 13, LED x 5
Displayable Language on LCD	US-English, Japanese US-English, French, German, Italian, Spanish, Chinese (simplified), Korean, Japanese (Kanji), Russian GAR0, HP-GL/2, HP RTL
Printer Language	
Interface	
USB	Built-in
Type	Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer
Mode	Series B (4 pins)
Connector type	
Ethernet	Built-in
Type	IEEE 802.3 10base-T, IEEE 802.3u 100base-TX / Auto-Negotiation
Standard	IEEE 802.3 x Full Duplex, IEEE 802.3ab 1000base-T/Auto-Negotiation
Protocol	IPX/SPX (Netware 4.2(J), 5.1(J), 6.0(J)) SNMP (Canon-MIB), HTTP, TCP/IP, AppleTalk
Operating Systems supported	
Windows	2000 (32)/XP (32 & 64)/Server 2003 (32 & 64)/Server 2008 (32 & 64)/Vista (32 & 64) OS X (32 & 64)
Macintosh	
Memory	256Mb
Standard Memory	iPF655 - 160Gb (including 8Gb Dynamic Memory)
HDD	
Print head	
Model	PF-04
Type	Bubble-jet on demand
Head configuration	6 colours integrated type (6 chips per print head)
Nozzle pitch	1,200dpi
Nozzle per chip	MBK: 5,120 nozzles, Other Colours: 2,560 nozzles each
Droplet size	4 pl per colour
Head replacement	User replacement

Ink tank	
Model	PFI-102 (130ml): MBK/BK/C/Y, PFI-104 (130ml): M
Media handling	
Roll paper	One roll, front-loading, front output
Cut sheet	Top-feeding, front output (Manual feed using media locking lever)
Media type	
Roll paper	Standard Paper 80gsm Standard Paper 90gsm Matt Coated Paper 90gsm Glossy Photo Quality Paper 190gsm / 240gsm / 300gsm Satin Photo Quality Paper 190gsm / 240gsm / 300gsm Pearl Photo Paper 260gsm Matt Coated Paper 120gsm / 140gsm / 180gsm Opaque White Paper 120gsm High Resolution Self-adhesive Graphic Paper 140gsm High Resolution Barrier Paper 180gsm Glossy Proofing Paper 195gsm Semi-Glossy Proofing Paper 195gsm / 255gsm
Media Size	
Roll paper (width)	ISO: A3, A2, A2+ A1 JIS: B2, B4 ARCH: 24" Others: 10", 14", 16", 17", Banner (300mm)
Cut sheet	ISO: A4, A3, A3+, A2, A2+, A1, B4, B3, B2 DIN: C4, C3, C2 JIS: B4, B3, B2 ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34" ARCH: 9 x 12", 12 x 18", 18 x 24", 24 x 36" Photo: 20 x 24", 18 x 22", 14 x 17", 12 x 16", 10 x 12", 10 x 15", 16 x 20" (US Photo size) Poster: 20 x 30", 300 x 900mm Others: 13 x 22", Roll paper & Cut sheet: 0.07 - 0.8mm
Media Thickness	
Maximum Outside Diameter of Roll Paper	150mm
Media Core Size	Internal diameter of roll core: 2" / 3"
Media Width	Roll paper: 254 - 609.6mm (24") Cut sheet: 203.2 - 609.6mm (24")
Minimum Regular Format Size (Vertical)	Roll Paper: 203.2mm (8") Cut Sheet: 279.4mm (11"): Letter size (long side)
Maximum Printable Paper Length	Roll paper: 18m (Varies according to the OS and application) Cut sheet: 1.6m (Varies according to the OS and application)
Margins (Top, Bottom, Sides)	
Recommended area	Roll paper: Top: 20mm, Bottom: 5mm, Side: 5mm Cut sheet: Top: 20mm, Bottom: 23mm, Side: 5mm
Printable area	Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless print): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet: Top: 3mm, Bottom: 23mm, Side: 3mm
Media width for borderless printing	10"(254mm), B4(257mm), A3(297mm), Banner(300mm), 14"(356mm), A2(420mm), A2+17"(432mm), B2(515mm), A1(594mm), 24"(610mm)
Option	
Roll Holder Set (2-inch core spindle with 3" core roll media)	RH2-26
Printer Stand/Basket	ST-26
Consumables	
Ink Tank	PFI-102 (130ml);MBK/BK/C/Y, PFI-104: M
Print Head	PF-04
Maintenance Cartridge	MC-10
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final are subject to change without notice.™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	
Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.	



Canon Inc.
canon.com
Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V., 2011

Canon (UK) Ltd
Woodhatch
Reigate, Surrey
RH2 8BF
Tel: 01737 220000
Fax: 01737 220022
www.canon.co.uk

Canon Ireland
Arena Road, Sandyford
Industrial Estate
Dublin 18, Ireland
Tel: 01 2052400
Fax: 01 2958141
www.canon.ie

