

Next generation document communication.

imageRUNNER ADVANCE C5000 Series

Introducing the new imageRUNNER ADVANCE multifunctional devices. Built to support your document workflows and enhance business communication they offer high productivity, exceptional quality whilst safeguarding your confidential information and providing environmental support.

UP TO **51ppm**
COLOUR AND
MONO

CHOICE OF 2
FIERY RIPS

1200DPI PRINTING

UP TO 5000 SHEET
PAPER CAPACITY

ADVANCED
FINISHING
CAPABILITY

COMPACT
DESIGN



Efficiency/Productivity

- Ability to scan and reuse hardcopy documents
- Personalised User interface
- High speed duplex scanning
- Advanced scanning into business applications
- Advanced fax capabilities

High Quality

- Superb print quality (1200dpi)
- Paper weights up to 256gsm
- Mixed media support
- Optional fiery controllers

Security

- Advanced security features to provide document confidentiality, integrity and availability
- Assists with compliance requirements

Compact and Modular

- Inner staple finisher
- Booklet & Staple finishing
- Hole Punch capability

Environmental

- Assistance in Environmental compliance
- Incorporating recycled materials like Bio plastics

Cost

- Integrated authentication software
- Shared device functionality reducing the need for unnecessary accessories

 **imageRUNNER**
ADVANCE

Canon

Specification: imageRUNNER ADVANCE C5000 Series

Type	Desktop (Reader/Printer separated)
Maximum Original Size	A3
Copy Sizes	Cassette 305 x 457mm, A3, A4, A4R, A5R Free size 139.7 x 182mm to 304.8 x 457.2mm optional Envelope Feeder DL, ISO-B5, ISO-C5 A5R - SRA3 (320 x 450mm), Envelopes Free size 99 x 140mm to 320 x 457mm
Resolution	Stack Bypass Reading 600dpi x 600dpi Copying 600dpi x 600dpi Printing 1200dpi x 1200dpi (text/line only) 256 Gradients
Copy/Print Speed	A4 C5051/i: 51ppm (B&W/Colour) C5045/i: 45ppm (B&W/Colour) C5035/i: 35ppm (B&W/Colour) C5030/i: 30ppm (B&W/Colour) A3 C5051/i: 26ppm (B&W/Colour) C5045/i: 26ppm (B&W/Colour) C5035/i: 18ppm (B&W/Colour) C5030/i: 18ppm (B&W/Colour)
Magnification	Zoom 25-400% Fixed 25%, 50%, 71%, 100%, 141%, 200%, 400%
First copy time	Black-and-White 4.0sec (51/45ppm model), 5.5sec (35/30ppm model) Full Colour 6.5sec (51/45ppm model), 8.9sec (35/30ppm model)
Warm-Up Time	38 seconds
Multiple Copies/Prints	1 to 999 sheets
Duplexing	Standard automatic stackless
Paper weight	Cassette 52 to 209gsm Stack Bypass 52 to 256gsm Duplex 52 to 209gsm
Paper Capacity	Standard 550 sheets x2 cassettes (80gsm) Stack Bypass: 100 sheets (80gsm) Optional 550 sheets x2 cassettes (80gsm) Paper Deck 2,700 sheets (80gsm) Total capacity 5,000 sheets
CPU	1.2GHz
Memory	2.5GB
Hard Disk Drive	80GB
Interface	Ethernet (1000Base-T/100Base-TX/10Base-T) Wireless LAN (IEEE802.11b/g, Optional), USB2.0
Power Supply	220-240V AC, 50/60Hz
Power Consumption	1.8kW max (51/45ppm), 1.3kW max (35/30ppm)
Dimensions (WxDxH)	620 x 760 x 982mm (with 1PDS) / 1230mm (with 1PDS & CFU) 620 x 735 x 938mm (with DADF) / 1186mm (with DADF & CFU) 620 x 735 x 826mm (with Platen cover) / 1074mm (with Platen cover & CFU)
Weight	Approx.170kg (with 1PDS) Approx.153kg (with DADF)
PRINT SPECIFICATION	
PDL	UFR II, PCL5c/6 (standard for all i model), Adobe PostScript 3 (standard for C5045i/C5051i)
Resolution	1200dpi x 1200dpi (Text/Line only), 600dpi x 600dpi
Memory	2.5GB (Uses Main unit RAM)
Hard Disk	80GB (Uses Main unit HDD)
CPU	Canon Custom Processor, 1.2GHz (Uses Main unit CPU)
PS Fonts	Roman 136
PCL Fonts	Roman93, Bitmap10, OCR2
Supported OS	PCL Windows 2000/XP/Server2003/Vista/Server2008/Win7 Adobe PostScript 3 Windows 2000/XP/Server2003/Vista/Server2008/Win7, Mac OS X (10.4.9 or later)
UFR II	Windows 2000/XP/Server2003/Vista/Server2008/Win7, Mac OS X (10.4.9 or later)
Mac-PPD	Mac OS 9.1 or later, Mac OS X (10.2.8 or later)
Interface	Ethernet (1000Base-T/100Base-TX/10Base-T) Wireless LAN (IEEE802.11b/g, Optional), USB2.0
Network Protocol	TCP/IP (LPD/Port9100/WSD/IPP/PPS/SMB/FTP), IPv6, IPX/SPX (NDS, Bindery), AppleTalk
Pull Scan	Network TWAIN Driver (75 to 600dpi 24bit colour /8bit grayscale/ 2bit Black & White)
imagePASS-B1	
PDL	PCL5c/6, Adobe PostScript 3
Resolution	1200dpi x 1200dpi, 600dpi x 600dpi
Memory	512MB+512MB (Option)
Hard Disk	80GB
CPU	Intel Celeron-M M440 1.86GHz
PS Fonts	136 Adobe PS Fonts
PCL Fonts	80 Agfa fonts
Supported OS	Windows 2000/XP/Server2003/Server2008/Vista/Vista SP1, Mac OS X 10.3.9 or later
Interface	Ethernet 1000Base-T/100Base-TX/10Base-T, USB
Network Protocol	TCP/IP (LPD/Port9100/PPS/SMB/FTP), Apple Talk
ColorPASS-GX300 (Optional for C5051)	
PDL	Adobe PostScript 3
Resolution	1200dpi x 1200dpi, 600dpi x 600dpi
Memory	2GB
Hard Disk	160GB
CPU	Intel Duo Core2 Xeon E8400 2x3.0Ghz
PS Fonts	136 Adobe PS Fonts
PCL Fonts	N/A
Supported OS	Windows 2000/XP/Server2003/Server2008/Vista/Vista SP1, Mac OS X 10.3.9 or later
Interface	Ethernet 1000Base-T/100Base-TX/10Base-T, USB, D-sub 15-pin connector
Network Protocol	TCP/IP (LPD/Port9100/PPS/SMB/FTP), Apple Talk

Send Specification (Standard)	Scan Speed (A4, 300dpi) 70ipm (Colour/B&W), 100ipm for Duplex scan by 1PDS Scan Resolution 100dpi, 150dpi, 200 x 100dpi, 200dpi, 200 x 400dpi, 300dpi, 400dpi, 600dpi Destinations E-Mail/Internet FAX (SMTP), PC (SMB, FTP), iWDM, WebDAV Address book LDAP, Local (Max.1800) File Format TIFF, JPEG, PDF, XPS, High compression PDF/XPS, PDF/A-1b, Optimize PDF for Web
Universal Send Advanced Feature Set-D1	File Format Outline PDF (Trace & Smooth), Searchable PDF/XPS, Reader Extensions PDF, Office Open XML
Universal Send Security Feature Set-D1	File Format Encrypted PDF, Device Signature PDF/XPS
Colour Image Reader Unit-B1	Paper size A3, A4, A4R, A5, A5R Single sided original 42 to 128gsm Double sided original 50 to 128gsm Max. Number of originals 100 sheets (80gsm) for 2-sided Double pass ADF 150 sheets (80gsm) for 1PDS
Document Scanning speed (max.)	2-sided Double pass ADF Copy A4 46ipm 600dpi (Colour/B&W) 2-sided Double pass ADF Scan A4 46ipm 300dpi (Colour/B&W) 1PDS Copy A4 51/70ipm 600dpi (Colour/B&W) 1PDS Scan A4 70ipm 300dpi (Colour/B&W), 100ipm 300dpi for Duplex scan
Dimensions (W x D x H)	2-sided Double pass ADF 620 x 536 x 137mm 1PDS 618 x 603 x 180mm
Weight	2-sided Double pass ADF Approx. 8.7kg 1PDS Approx. 26.8kg
Cassette Feeding Unit AD1	Type 2 Front-loading adjustable drawers Paper Size 305 x 457mm, A3, A4, A4R, A5R Free size 139.7 x 182 mm to 304.8 x 457.2 mm Paper Weight 52 to 209gsm Paper Capacity 550 sheets (80gsm) x 2 cassettes Dimensions (W x D x H) 620 x 700 x 251mm Weight Approx. 27.5 kg
Paper Deck Unit B1	Paper Size A4 Paper Weight 52 to 163gsm Paper Capacity 2,700 sheets (80gsm) Dimensions (W x D x H) 372 x 603 x 473mm Weight Approx. 37 kg
Inner Finisher A1	Number of trays One stack tray (Optional 2nd Tray) Tray capacity A4, A5, A5R A4-A5R: 500 sheets A3, A4R A3, A4R: 500 sheets Staple position Corner, Double Staple capacity A4: 50 sheets A3: 30 sheets Dimensions (W x D x H) 865 x 540 x 234mm Weight Approx. 11.5kg (Approx.13kg with optional tray)
Staple Finisher C1/Booklet Finisher C1	Number of trays 2 Trays Tray capacity A4, A5, A5R 1300 on upper tray, 1700 on lower tray A3, A4R 650 on upper tray, 650 on lower tray Staple position Corner, Double, Booklet stitch (Booklet Finisher only) Staple capacity A4 50 sheets (80gsm) A3, A4R 30 sheets (80gsm) Booklet Stitch Specifications (Booklet Finisher only) Paper size 305 x 457mm, A3, A4R Staple capacity 1 to 16 sheets (64 pages, 52-81gsm) 1 to 10 sheets (40 pages, 82-105gsm) Dimensions (W x D x H) Staple Finisher 677 x 646 x 1097mm Booklet Finisher 789 x 646 x 1097mm Weight Staple Finisher Approx. 46kg Booklet Finisher Approx. 75kg
Optional Accessories	Colour Image Reader Unit B2, Printer Cover C1, Direct Print Kit H1, Barcode Printing Kit D1, Data Erase Kit C1, HDD Data Encryption & Mirroring Kit C1, Encrypted Printing Software D1, Secure Watermark B1, Web Access Software H1, Access Management System Kit B1, Expansion Bus F1, Wireless LAN Board B1, IPsec Board B2, 2.5inch/80GB HDD C1, 2.5inch/250GB HDD D1, Removable HDD Kit AC1, Document Scan Lock Kit A1, Super G3 Fax Board AE1, Super G3 2nd Line Fax Board AE1, Universal Send Digital User Signature Kit C1, Remote Fax Kit A1, Plain Pedestal, Envelope Feeder Attachment D1, Tab Feeding Attachment Kit B1, Copy Tray J1, Inner 2 Way Tray F1, External 2 Hole Puncher B1, External 2/4 Hole Puncher B1, External 4 Hole Puncher B1, Inner Finisher Additional Tray A1, Utility Tray A1, Key Switch Unit A2, Copy Card Reader Attachment B1, Card Reader C1, Remote Operators Software Kit B1, Voice Guidance Kit F1, Voice Operation Kit C1, USB Device Port B1, Multimedia Reader/Writer A1.
This leaflet and the specifications of the product have been developed prior to the date of product launch. These specifications are subject to change without notice. Therefore no representations or warranties, either express or implied, are made of the fitness of this product for a particular purpose. In no circumstances shall the information in this leaflet be considered part of our terms and conditions of sale. You are advised to check the prevailing specification immediately prior to purchase. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	

